

CLEAF KRISTALL

Kristall is a shiny surface for furniture and interior design available as faced panel and edge. ABS-PMMA sheets guarantee excellent aesthetic characteristics, good resistance to scratches and high resistance to light and stains. All faced panels feature a protection film on both sides.

TECHNICAL CHARACTERISTICS	FACED PANEL		EDGE BAND
	STANDARD	LEVEL	LEVEL
SIZES *		2790 x 1300 mm	blister h 24 and 27 mm
THICKNESSES *		19 – 22 mm	1,0 mm
GLOSS 60°	ISO2813	≥ 85	≥ 85
RESISTANCE TO SCRATCHES	EN14323	≥ Level 3 ≥ 4N	≥ Level 3 ≥ 4N
RESISTANCE TO STAINS	EN14323	Groups 1 and 2, class ≥ 4	Groups 1 and 2, class ≥ 4
RESISTANCE TO LIGHT	EN14323	> 6 blue wool scale	≥ 6 blue wool scale
FORMALDEHYDE EMISSION	EN ISO 12460-3	Made with panels E1 and CARB P2 TSCA Title VI	It doesn't contain formaldehyde
COLOUR TOLERANCES		DE < 0,8	DE < 1,5

*

Values reported herein are related to a standard product configuration. For customized non-standard products, please contact our Sales Office.



STORAGE AND HANDLING

Goods must be stored in a dry and ventilated place (relative air humidity 35%-65%). Do not store with inflammable substances. If exposed to direct sunlight, the panel may deteriorate. Stacks should be stored correctly, at a manageable height to ensure stability. To avoid warping or damp stains, place the panels on pallets with adequate spaces. When handling the panels, use suction pads or gloves. Machinery and equipment must be fitted with suitable aspiration systems.



CLEANING & MAINTENANCE

Kristall panel is delivered with a protective film that needs to be removed immediately after assembly. For cleaning, it is preferable to choose a detergent for domestic use. It is recommended that you avoid spraying products directly onto the surface, as this may leave stains and marks; instead, it is preferable to apply the detergent product on a soft damp cloth, clean the surface and then rinse it. Avoid using abrasive products, bleach or highly chlorinated products or acids.