



HYPERFLEX LAMINATE

Hyperflex is an ultra-thin decorative laminate. Thanks to its excellent flexibility, it is the ideal product for coating profiles, skirting boards and the top of wardrobes. It is not necessary to apply further coating since the high-resistance properties of the product are already sufficient in order to protect its surface.

It is available in three versions:

HYPERFLEX R1

Thickness 0,10mm, single layer.

HYPERFLEX R2

Thickness 0,15mm. Thanks to the 30g/m² TNT support, the product is ideal for coating moulded door panels and for any other application requesting a higher resistance compared to product R1.

HYPERFLEX R3

Thickness 0,18mm. Supported by parchment of 70gr/m². This product is ideal for wrapping profile and frames with multiple curves and very sharp radiuses, as well as in cases where defects of support (such as matching of MDF + pine) request a product with a higher covering ability.



TECHNICAL CHARACTERISTICS

SIZES FOR SURFACES	Rolls of 1300mm	
THICKNESS	Nominal thickness +/-0,05mm	
FINISH	matt, semi matt or gloss	
TEXTURE	flat or textured	
RESISTANCE TO ABRASION	UNI 9115	Level \geq 4
TENDENCY TO RETAIN DIRT	UNI 9300	Level \geq 4
RESISTANCE TO SCRATCHES	UNI 9428	Level \geq 3
RESISTANCE TO STAINS	EN 14323	Group 1 \geq 4; Group 2 \geq 3
RESISTANCE TO LIGHT	UNI 9427	\geq 5 grayscale
FORMABILITY (method A)	EN 438/2-32	Any radius
FORMALDEHYDE EMISSION	EN 717-2	\leq 3,5 mg/hm ²



ON REQUEST

CHPL FSC CERTIFIED
FSC CW ICILA-CW-000343

CLEAF

HYPERFLEX LAMINATE



STORAGE AND HANDLING

Goods must be stored in a dry and ventilated place (relative air humidity 35%-65%). Do not store with inflammable substances. If exposed to direct sunlight, the laminate may deteriorate. Stacks should be stored correctly, at a manageable height to ensure stability. When handling the laminates, use suction pads or gloves. Machinery and equipment must be fitted with suitable aspiration systems.



CLEANING & MAINTENANCE

For cleaning, it is preferable to choose a detergent for domestic use. It is recommended that you avoid spraying products directly onto the surface, as this may leave stains and marks; instead, it is preferable to apply the detergent product on a soft damp cloth, clean the surface and then rinse it. Avoid using abrasive products, bleach or highly chlorinated products or acids.